

MATERIAL SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Discool
Supplier: Cammann Inc.
P.O. Box 219
7105 State 60
Birmingham, Ohio 44816
Emergency Phone: 440-965-4051

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Names and Synonyms: Severe Treat Min. Oils & Additives

Globally Reportable MSDS Ingredients:

<u>Substance Name</u>	<u>Approx Wt.</u>
Carboxylic Acid Anhydride	5-15

See Section 8 for exposure limits (if applicable)

3. HAZARDS IDENTIFICATION

This product may be considered hazardous according to regulatory guidelines (See Section 15).

EMERGENCY OVERVIEW: Amber Liquid. DOT ERG No. : NA

POTENTIAL HEALTH EFFECTS: This product may be used in certain applications where misting can occur. Excessive exposure to liquids and mists may cause skin and eye irritation. In addition, excessive exposure to mists may cause respiratory irritation and damage and aggravate pre-existing emphysema or asthma.

For further health effects/ toxicological data. See Section 11.

4. FIRST AID MEASURES

EYE CONTACT: Flush thoroughly with water. If irritation occurs, call a physician.

SKIN CONTACT: Wash contact areas with soap and water. Remove and clean oil soaked clothing daily and wash affected area. (See Section 16 – Injection Injury).

INHALATION: If respiratory irritation, dizziness, nausea, or unconsciousness occurs due to excessive vapor or mist exposure, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or mouth-to-mouth resuscitation.

INGESTION: Not expected to be a problem. Seek medical attention if discomfort occurs. Do not induce vomiting.

NOTE TO PHYSICIANS: Pre-existing conditions which may be aggravated by exposure include emphysema and asthma.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical and water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Water or foam may cause frothing. Use water to keep fire exposed containers cool. Water spray may be used to flush spills away from exposure. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

SPECIAL PROTECTIVE EQUIPMENT: For fires in enclosed areas, fire fighters must use self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

COMBUSTION PRODUCT: Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

Flash Point: C(F): 177(350) (ASTM D-92)

Flammable Limits (approx. % vol. in air) – LEL: NE, UEL: NE

NFPA HAZARD ID: Health: 0 Flammability: 1, Reactivity: 0

6. ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES: Report spills/ releases as required to appropriate authorities. U.S. Coast Guard and EPA regulations require immediate reporting of spills/releases that could reach any waterway including intermittent dry creeks. Report spill/release to Coast Guard National Response Center toll free number (800) 424-8802. In case of accident or road spill notify CHEMTREC (800) 424-9300.

PROCEDURES IF MATERIAL IS RELEASED OR SPILLED:

LAND SPILL: Shut off source taking normal safety precautions. Take measures to minimize the effects on ground water. Recover by pumping or contain spilled liquid with sand or other suitable absorbent and remove mechanically into containers. If necessary, dispose of absorbed residues as directed in Section 13.

WATER SPILL: This product emulsifies with water and is totally miscible. If spilled, shut off source and seek advice from a specialist. Notify relevant authorities.

ENVIRONMENTAL PRECAUTIONS: Prevent material from entering sewers, water sources or low lying areas; advise the relevant authorities if it has, or if it contaminates soil/vegetation.

PERSONAL PRECAUTIONS: See Section 8

7. HANDLING AND STORAGE

HANDLING: Avoid inhalation of vapors or mists. See Section 8 for additional personal protection advice when handling this product.

STORAGE: Keep containers closed when not in use. Do not store in open or unlabelled containers. Store away from strong oxidizing agents and combustible materials. Do not store near heat, sparks, flame or strong oxidants.

SPECIAL PRECATUIONS: Prevent small spills and leakages to avoid slip hazard.

EMPTY CONTAINER WARNING: Empty containers retain residue (Liquid and/or vapor) and can be dangerous. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.** Do not attempt to refill or clean container since residue is difficult to remove. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS:

When mists/aerosols can occur, the following are recommended: 5 mg/m³ (as oil mist) – ACGIH Threshold Limit value (TLV), 10 mg/m³ (as oil mist) – ACGIH Short Term Exposure Limit (STEL), 5 mg/m³ (as oil mist) – OSHA Permissible Exposure Limit (PEL)

VENTILATION: Use adequate ventilation, local exhaust, or enclosures to control below exposure limits.

RESPIRATORY PROTECTION: When ventilation is not adequate, wear approved respirator.

EYE PROTECTION: Chemical type goggles should be worn during misting operations. Normal industrial eye protection practices should be employed for other use conditions.

SKIN PROTECTION: Not normally required. When splashing or liquid contact can occur frequently, wear oil resistant gloves and/or other protective clothing. Good personal hygiene practices should always be followed.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical physical properties are given below. Consult Product Data Sheet for specific details.

APPEARANCE: Liquid

COLOR: Amber

ODOR: Sweet

ODOR THRESHOLD – ppm: NE

pH: NE

BOILING POINT C(F): > 100 (212)

MELTING POINT C(F): NA

FLASH POINT C(F): 177 (350) (ASTM D-92)

FLAMMABILITY (solids): NE

AUTO FLAMMABILITY C(F): NA

EXPLOSIVE PROPERTIES: NA

OXIDIZING PROPERTIES: NA

VAPOR PRESSURE – mmHg 20C : NE

VAPOR DENSITY: > 2.0
EVAPORATION RATE: NE
RELATIVE DENSITY, 15/4 C: 0.893
SOLUBILITY IN WATER: Emulsifies
PARTITION COEFFICIENT: NE
VISCOSITY at 40 C, cSt: > 20.0
VISCOSITY at 100 C, cSt: NE
POUR POINT C (F): NE
FREEZING POINT C (F): NE
VOLATILE ORGANIC COMPOUND: NE
DMSO EXTRACT, IP-346 (WT.%): <3, for mineral oil only
NA=NOT APPLICABLE NE=NOT ESTABLISHED D=DECOMPOSES

For further technical information, contact your marketing representative

10. STABILITY AND REACTIVITY

STABILITY (THERMAL, LIGHT, ETC.): Stable.

CONDITIONS TO AVOID: Extreme heat and high energy sources of ignition. Freezing temperatures.

IMCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Product does not decompose at ambient temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL DATA

--ACUTE TOXICOLOGY--

ORAL TOXICITY (RATS): Practically non-toxic (LD50: greater than 2000 mg/kg). – Based on testing of similar products and/or the components.

DERMAL TOXICITY (RABBITS): Practically non-toxic (LD50: greater than 2000 mg/kg) – Based on testing of similar products and/or the components.

INHALATION TOXICITY (RATS): Practically non-toxic (LC50: greater than 5 mg/1).- Based on testing of similar products and/or the components.

EYE IRRITATION (RABBITS): Practically non-irritating (Draize score: greater than 6 but 15 or less). – Based on testing of similar products and/or the components.

SKIN IRRITATION (RABBITS): Practically non-irritating (Primary Irritation Index: greater than 0.5 but less than 3). – Based on testing of similar products and/or the components.

CHRONIC TOXICOLOGY (SUMMARY)

Repeated and/or prolonged exposure may cause irritation to the skin, eyes or respiratory tract. Overexposure to oil mist may result in oil droplet deposition and/or granuloma formation. The base oils in this product are severely solvent refined and/or severely hydrotreated. Chronic mouse skin painting studies of severely treated oils showed no evidence of carcinogenic effects.

OTHER TOXICOLOGY DATA

Small metal particles from machining may cause abrasion of the skin and may predispose to dermatitis.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE AND EFFECTS:

ECOTOXICITY: Not established.

MOBILITY: Not established.

PERSISTENCE AND DEGRADABILITY: Not established.

BIOACCUMULATIVE POTENTIAL: Not established.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Product is suitable for burning in an enclosed, controls burner for fuel value. Such burning may be limited pursuant to the Resource Conservation and Recovery Act. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate government waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

RCRA INFORMATION: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D) nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity. The unused product is not formulated with substances covered by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

14. TRANSPORT INFORMATION

USA DOT: NOT REGULATED BY USA DOT

RID/ADR: NOT REGULATED BY RID/ADR

IMO: NOT REGULATED BY IMO

IATA: NOT REGULATED BY IATA

STATIS ACCUMULATOR (50 picosiemens or less): YES

15. REGULATORY INFORMATION

US OSHA HAZARD COMMUNICATION STANDARD: This product may be used in certain applications where misting can occur. According to OSHA 29 CFR 1910.1200, certain mineral oil mists may be considered hazardous if the workplace airborne concentration exceed 5 mg/m3 (ACGIH TLV).

EU Labeling: Product is not dangerous as defined by the European Union Dangerous Substances/Preparations Directives. EU labeling not required.

Governmental Inventory Status: All components comply with TSCA.

U.S. Superfund Amendments and Reauthorization Act (SARA) Title III: This product contains no "EXTREMELY HAZARDOUS SUBSTANCES".

SARA (311/312) REPORTABLE HAZARD CATEGORIES: None.

This product contains no chemical subject to the supplier notification requirements of SARA (313) toxic release program.

The following product ingredients are cited on the lists below:

<u>CHEMICAL NAME</u>	<u>CAS NUMBER</u>	<u>LIST CITATIONS</u>
MALETIC ANHYDRIDE	108-31-6	1

REGULATORY LISTS SEARCHED

1=ACGIH ALL	6=IARC 1	11=TSCA 4	16=CA P65 CARC	21=LA RTK
2=ACGIH A1	7=IARC 2A	12=TSCA 5a2	17=CA P65 REPRO	22=MI 293
3=ACGIH A2	8=IARC 2B	13=TSCA 5e	18=CA RTK	23=MN RTK
4=NTP CARC	9=OSHA CARC	14=TSCA 6	19=FL RTK	24=NJ RTK
5=NTP SUS	10=OSHA Z	15=TSCA 12b	20=IL RTK	25=PA RTK
				26=RI RTK

*EPA recently added new chemical substances to its TSCA section 4 test rules. Please contact the supplier to confirm whether the ingredients in this product current appear on a TSCA 4 or TSCA 12b list.

Code key: CARC=Carcinogen; SUS-Suspected Carcinogen; REPRO=Reproductive

16. OTHER INFORMATION

USE: WATER MISCIBLE CUTTING FLUID

NOTE: PRODUCTS OF CAMMANN INC., ARE NOT FORMULATED TO CONTAIN PCBS.

Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. Information provided on this MSDS reflects intended use. This product should not be used for other applications. In any case, the following advice should be considered:

INJECTION INJURY WARNING: If product is inject into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

Precautionary Label Text:

CAUTION:

Excessive exposure to liquids and mists may cause skin and eye irritation. In addition, excessive exposure to mists may cause respiratory irritation and damage and aggravate pre-existing emphysema and asthma.

Keep container closed. Use with adequate ventilation.

FIRST AID: If inhaled and symptoms develop, remove to fresh air and get medical attention.

For industrial use only. Not intended or suitable for use in or around a household or dwelling.

Refer to product Material Safety Data Sheet for further safety and health information.

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control: all risks of use of the product are therefore assumed by the user and **WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT.** Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. Cammann Inc. and its affiliated companies assume no responsibility for accuracy of information unless the document is the most current available from an official Cammann distribution system. Cammann and its affiliated companies neither represent nor warrant that the format, content or product formulas contained in this document comply with the laws of any other country except the United States of America.

Prepared by: Cammann Inc.
August 19, 2008